

Amendment & Response***Application No.: 09/712,237
Page 3*****IN THE CLAIMS:****Please amend claim 24 as follows:**

1. (Previously Canceled)
2. (Previously Canceled)
3. (Previously Canceled)
4. (Previously Canceled)
5. (Previously Canceled)
6. (Previously Canceled)
7. (Previously Canceled)
8. (Previously Canceled)
9. (Previously Canceled)
10. (Previously Canceled)
11. (Previously Canceled)
12. (Previously Canceled)
13. (Previously Canceled)
14. (Previously Canceled)
15. (Previously Canceled)
16. (Previously Canceled)
17. (Previously Canceled)
18. (Previously Canceled)
19. (Previously Canceled)
20. (Previously Canceled)
21. (Previously Canceled)
22. (Previously Canceled)
23. (Previously Canceled)

Cancel claim 24-31, Amend claims 32 and 33, Add claims

24. (currently amended) A flow regulator, [compromising] comprising:

Amendment & Response***Application No.: 09/712,237
Page 4***

- a membrane having at least one hole;
- a bottom layer comprising an outlet; and
- a fluid pathway;

the membrane being positioned above the bottom layer, the fluid pathway [begin] being defined from above the membrane [thorough] through the hole and along the bottom layer on the side facing the membrane and through the outlet, wherein flow through the hole causes the membrane to deflect and engage against at least on portion of the bottom layer thereby impeding the fluid pathway by impeding flow through the hole in the membrane while not impeding the outlet.

25 (previously added) A flow regulator according to claim 24, wherein the side of the bottom layer facing the membrane further compromises at least one channel which constitutes a part of the fluid pathway, the first end of the channel being in connection with an outlet port, wherein flow through the hole causes the membrane to deflect and engage against at least one portion of the bottom layer thereby forcing the fluid in this portion to flow only in the channel.

26. (previously added) A flow regulator according [ot] to claim 25, where in the shape and length of the channel are so designed that an increase of pressure generates an increase of the contact area between the [nembrane] membrane and the bottom layer, thereby defining an additional segment to the channel where fluid is confined, said configuration allowing a proper adjustment of the flow versus pressure characteristics.

- 27. (previously added) A flow regulator according to claim 26, where in the section of the channel is constant.
- 28. (previously added) A flow regulator according to claim 26, where in the shape and length of the channel are so designed that the fluid resistance is proportional to the pressure, implying thereby a flow rate independent of the pressure.
- 29. (previously added) A flow regulator according to claim 27 or 28, wherein the channel is spiral shaped groove.

Amendment & Response***Application No.: 09/712,237
Page 5***

30. (previously amended) A flow regulator according to any of claims 24 to 28, wherein the membrane further includes means for sensing the deflection of the membrane.
31. (previously amended) A flow regulator according to any of claims 24 to 28, wherein the fluid pathway is obstructed when the membrane has reached a predetermined degree of deflection.
32. (previously added) A flow regulator, comprising:
a membrane having at least one hole;
a bottom layer; and
a fluid pathway;
the membrane being positioned above the bottom layer, the fluid pathway being defined from above the membrane through the hole and along the bottom layer on the side facing the membrane, wherein flow through the hole causes the membrane to deflect and engage against at least one portion of the bottom layer thereby impeding the fluid pathway,
wherein the side of the bottom layer facing the membrane further comprises at least one channel which constitutes a part of the fluid pathway, the first end of the channel being in connection with an outlet port, wherein flow through the hole causes the membrane to deflect and engage against at least one portion of the bottom layer thereby forcing the fluid in this portion to flow only in the channel,
wherein the shape and length of the channel are so designed that an increase of pressure generates an increase of the contact area between the membrane and the bottom layer, thereby defining an additional segment of the channel where fluid is confined, said configuration allowing a proper adjustment of the flow versus pressure characteristics,
wherein a section of the channel is constant and the channel is spiral shaped groove.
33. (previously added) A flow regulator, comprising:
a membrane having at least one hole;
a bottom layer; and

Amendment & Response***Application No.: 09/712,237
Page 6***

a fluid pathway;
the membrane being positioned above the bottom layer, the fluid pathway being defined from above the membrane through the hole and along the bottom layer on the side facing the membrane, wherein flow thorough the hole causes the membrane to deflect and engage against at least one portion of the bottom layer there by impeding the fluid pathway,

wherein the side of the bottom layer facing the membrane further compromises at least one channel which constitutes a part of the fluid pathway, the first end of the channel being in connection with an outlet port, wherein flow through the hole causes the membrane to deflect and engage against at least one portion of the bottom layer thereby forcing the fluid in this portion to flow only in the channel,

wherein the shape and length of the channel are so designed that an increase generates an increase of the contact area between the membrane and the bottom layer, thereby defining an additional segment to the channel where fluid is confined, said configuration allowing a proper adjustment of the flow versus pressure characteristics,

wherein the shape and length of the channel are so designed that the fluid resistance is proportional to the pressure, implying thereby a flow rate independent of the pressure and the channel is a spiral shaped groove.